

===== MSDS =====  
Safety Information  
=====

[TOP](#)

FSC: 6850

MSDS Date: 05/30/1991

MSDS Num: BPSDC

Submitter: F BT

LIIN: 00F025515

Tech Review: 11/16/1992

Status CD: C

Product ID: 2X727-A CLASS F RED INS EN

MFN: 01

Article: N

Kit Part: N

Responsible Party

Cage: 09800

Name: SPRAYON PRODUCTS

Address: 26300 FARGO AVE

Box: N/K

City: BEDFORD HTS

State: OH

Zip: 44146-1310

Country: US

Info Phone Number: 216-292-7400

Emergency Phone Number: 216-292-7400

Preparer's Name: N/P

Proprietary Ind: N

Review Ind: Y

Published: Y

Special Project CD: N

===== Preparer =====  
Co. when other than Responsible Party Co.  
=====

[TOP](#)

Cage: 09800

Assigned Ind: N

Name: SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address: 26300 FARGO AVENUE

Box:

City: BEDFORD HEIGHTS

State: OH

Zip: 44146

===== Contractor =====  
Summary  
=====

[TOP](#)

Cage:09800

Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE

City:BEDFORD HEIGHTS

State:OH

Zip:44146

Country:US

Phone:216-292-7400 OR 216-595-8634

===== Ingredients =====  
=====

[TOP](#)

Cas: 1330-20-7

Code: M

RTECS #: ZE2100000

Code: M

Name: XYLENE, DIMETHYLBENZENE, XYLOL

% Text: 15%

Environmental Wt:

Other REC Limits: 100 PPM

OSHA PEL: 100 PPM

Code: M

OSHA  
STEL:

Code:

ACGIH TLV: 100 PPM, SKIN

Code: M

N/P

Code:

EPA Rpt Qty: 1000 LBS

ACGIH  
STEL:  
DOT Rpt 1000 LBS  
Qty:

Ozone Depleting Chemical: N

Cas: 108-88-3

Code: M

RTECS #: XS5250000

Code: M

Name: TOLUENE

% Text: 5%

Environmental Wt:

Other REC Limits: 375 MG/CUM

OSHA PEL: 200 PPM/150 STEL

Code: M

OSHA  
STEL:

Code:

ACGIH TLV: 50 PPM; 9293

Code: M

ACGIH N/P  
STEL:

Code:

EPA Rpt Qty: 1000 LBS

DOT Rpt 1000 LBS  
Qty:

Ozone Depleting Chemical: N

Cas: 67-64-1

Code: M

RTECS #: AL3150000

Code: M

Name: ACETONE; DIMETHYL KETONE

% Text: 15%

Environmental Wt:

Other REC Limits: N/K

OSHA PEL: 1000PPM

Code: M

OSHA  
STEL:

Code:

ACGIH TLV: 750PPM/1000STEL;9293

Code: M

ACGIH N/P  
STEL:

Code:

EPA Rpt Qty: 5000 LBS

DOT Rpt 5000 LBS  
Qty:

Ozone Depleting Chemical: N

Cas: 64742-95-6

Code: M

RTECS #: WF3400000

Code: M

Name: SOLVENT NAPHTHA, PETROLEUM, LIGHT AROMATIC, HIGH FLASH AROMATIC NAPHTHA

% Text: <5%

Environmental Wt:

Other REC Limits: N/K

OSHA PEL: N/K

Code: M

OSHA  
STEL:

Code:

ACGIH TLV: N/K

Code: M

ACGIH N/P  
STEL:

Code:

EPA Rpt Qty:

DOT Rpt  
Qty:

Ozone Depleting Chemical: N

Cas: 75-09-2

Code: M

RTECS #: PA8050000

Code: M

Name: DICHLOROMETHANE (METHYLENE CHLORIDE) (SUSPECTED HUMAN CARCINOGEN BY ACGIH, NTP)

% Text: 20%

Environmental Wt:

Other REC Limits: N/K

OSHA PEL: 500 PPM

Code: M

OSHA  
STEL:

Code:

ACGIH TLV: 174 MG/CUM (A2)

Code: M

ACGIH N/P  
STEL:

Code:

EPA Rpt Qty: 1000 LBS

DOT Rpt 1000 LBS  
Qty:

Ozone Depleting Chemical: N

Cas: 75-28-5

Code: M

RTECS #: TZ430000

Code: M

Name: ISOBUTANE, 2-METHYLPROPANE

% Text: 10%

Environmental Wt:

Other REC Limits: 1000 PPM

OSHA PEL: 1800 MG/CUM

Code: M

OSHA  
STEL:

Code:

ACGIH TLV: 1000 PPM

Code: M

ACGIH N/P  
STEL:

Code:

EPA Rpt Qty:

DOT Rpt  
Qty:

Ozone Depleting Chemical: N

Cas: 74-98-6

Code: M

RTECS #: TX2275000

Code: M

Name: PROPANE

% Text: 10%

Environmental Wt:

Other REC Limits: 1800 MG/CUM

OSHA PEL: 1000 PPM

Code: M

OSHA  
STEL:

Code:

ACGIH TLV: SIMPLE ASPHYXIANT

Code: M

ACGIH N/P  
STEL:

Code:

EPA Rpt Qty:

DOT Rpt  
Qty:

Ozone Depleting Chemical: N

=====  
Hazards Data  
===== Health

[TOP](#)

LD50 LC50 Mixture N/K

Route Of Entry Inds – Inhalation: YES

Skin: NO

Ingestion: YES

Carcinogenicity Inds – NTP: YES

IARC: NO

OSHA: NO

Health Hazards Acute And Chronic

SKIN: IRRITATION. INHALATION: UPPER RESPIRATORY SYSTEM IRRITATION, ANESTHETIC EFFECTS.

Explanation Of Carcinogenicity

SEE INGREDIENTS

Signs And Symptoms Of Overexposure

INHALATION: LIGHT-HEADEDNESS, STAGGERING GAIT, GIDDINESS, NAUSEA, PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INGESTION: KIDNEY/LIVER DAMAGE, HARMFUL OR FATAL.

Medical Cond Aggravated By Exposure

CARDIOVASCULAR PROBLEMS MAY BE AGGRAVATED BY OVEREXPOSURE TO METHYLENE CHLORIDE.

First Aid

INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH W/WATER FOR 15 MIN. SKIN: WASH W/SOAP & WATER. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Spill Release Procedures

REMOVE ALL SOURCES OF IGNITION, VENTILATE, AVOID BREATHING VAPORS & REMOVE W/INERT ABSORBENT.

Neutralizing Agent

N/K

### Waste Disposal Methods

DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. DON'T PUNCTURE OR INCINERATE.

### Handling And Storage Precautions

DON'T STORE >120F. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR HEAT MAY CAUSE BURSTING.

### Other Precautions

KEEP AWAY FROM CHILDREN. DON'T PUNCTURE OR INCINERATE. DON'T SPRAY NEAR FIRE OR OPEN FLAME.

## Explosion Hazard Information

Fire and

[TOP](#)

Flash Point Method: TOC

Flash Point:

Flash Point Text: <20F PROPELLANT

Autoignition Temp:

Autoignition Temp Text: N/A

Lower Limits: N/K

Upper Limits: N/K

### Extinguishing Media

CO2, DRY CHEMICAL OR FOAM

### Fire Fighting Procedures

WATER MAY BE INEFFECTIVE. WATER MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL.

### Unusual Fire/Explosion Hazard

DON'T SPRAY NEAR OPEN FLAME. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR OTHER HEAT MAY CAUSE BURSTING.

Measures

Control

[TOP](#)

### Respiratory Protection

WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA IF EXPOSURE CANNOT BE CONTROLLED BELOW TLV. WHEN SANDING OR ABRADING THE DRIED FILM, WEAR A DUST/MIST RESPIRATOR APPR OVED BY NIOSH/MSHA.

### Ventilation

LOCAL EXHAUST

### Protective Gloves

RECOMMENDED

### Eye Protection

SAFETY GLASSES W/UNPERFORATED SIDESHIELD

### Other Protective Equipment

FACE SHIELD & APRON.

### Work Hygienic Practices

N/K

Supplemental Safety and Health

AEROSOL-CONTENTS UNDER PRESSURE.

Physical/Chemical Properties

TOP

HCC:

NRC/State LIC No:

Net Prop WT For Ammo:

Boiling Point:

B.P. Text: <0F PROPEL

Melt/Freeze Pt:

M.P/F.P Text: N/R

Decomp Temp:

Decomp Text: N/K

Vapor Pres: 50-60 PSIG

Vapor Density: >1

Volatile Org Content %:

Spec Gravity: N/R

VOC Pounds/Gallon:

PH: N/K

VOC Grams/Liter:

Viscosity: N/P

Evaporation Rate & Reference: FASTER THAN ETHER

Solubility in Water: N/R

Appearance and Odor: COATINGS

Percent Volatiles by Volume: 81%/WT

Corrosion Rate: N/K

Data Reactivity

TOP

Stability Indicator: YES

Stability Condition To Avoid: OPEN FLAME, DIRECT SUNLIGHT, TEMPS. >120F & ALL SOURCES OF IGNITION.

Materials To Avoid: N/K

Hazardous Decomposition Products: BY OPEN FLAME: CO, CO2, HYDROGEN CHLORIDE & PHOSGEN GAS.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization N/K

Toxicological Information

TOP

Toxicological Information: N/P

Ecological Information

TOP

Ecological: N/P

Transport Information MSDS

TOP

Transport Information: N/P

Information

Regulatory

[TOP](#)

Sara Title III Information: N/P

Federal Regulatory Information: N/P

State Regulatory Information: N/P

Information

Other

[TOP](#)

Other Information: N/P

=====  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.