

Material Safety Data Sheet

may be used to comply with

A Hazard Communication Standard.

29 CFR 1910.1203 Standard must be
consulted for specific requirements

U.S. Department of Labor

Occupational Safety and Health Administration

(Non-Mandatory Form)



IDENTITY (as listed on Label and List)

ChamPADco Padding Cement

Note: Blank spaces are not intended. If any data is not applicable or no
information is available, the space must be marked to indicate that

Section I A Compounded Polyvinyl Acetate Base Adhesive

Manufacturer's Name

Champion Mfg. Co.

Emergency Telephone Number

Chemtrec 1-800-424-9300

Address (Number, Street, City, State, and ZIP Code)

Telephone Number for Information

425 W. 32nd St.

704-333-3797

Date Prepared

Jan. 2, 1991

Signature of Preparer (optional)

P. O. Box 18623, Zip Code 28218

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))

OSHA PEL

ACGIH TLV

Other Limits
Recommended

% (optional)

Dibutyl Phthalate CAS No. 84-74-2

5 mg./m³

5 mg./TWA

Approx. 8.0%

Dibutyl phthalate listed in this section is subject to the reporting requirements
of section 313 of the Superfund Amendments and Reauthorization Act (SARA) of 1986
and 40CFR372

Section III - Physical/Chemical Characteristics

Boiling Point

Water Approx.

212 deg. F.

Specific Gravity (H₂O = 1)

Approx.

1.02-1.08

Vapor Pressure (mm Hg)

20 deg. C. Approx.

17.6

Melting Point

N/A

Vapor Density (AIR = 1)

20 deg. C. Approx.

.9976

Evaporation Rate

(Butyl Acetate = 1)

Not
determined

Solubility in Water

Completely miscible with water. Thin only with water when necessary.

Appearance and Odor

Liquid-White Or Colors (Red- Blue- Green- Yellow) Mild Odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)

N/A

Flammable Limits

N/A

LEL

UEL

Extinguishing Media

Foam, Dry Chemical, Water Spray, CO₂

Special Fire Fighting Procedures

Fire fighters should wear self contained breathing apparatus to avoid inhalation of smoke

or vapors if material is involved in general fire.

Unusual Fire and Explosion Hazards

Non-flammable --None known

NFPA Hazard Code: 1 Health, 1 Fire, 0 Reactivity

(Reproduce locally)

OSHA 174, Sept 1985

Section V -- Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	None Known

Reactivity (Materials to Avoid)

None known

Hazardous Decomposition or Byproducts

Under severe thermal degradation - low molecular weight hydrocarbon may be formed.

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	N/A

Section VI -- Health Hazard Data

Routes of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Not expected
Health Hazards (Acute and Chronic)			

Eyes - may cause irritation - skin - may be irritating on continued or prolonged contact.

Do not take internally.

Carcinogenicity	NTP? N/A	IARC Monographs? N/A	OSHA Required? Not listed
-----------------	-------------	-------------------------	------------------------------

Signs and Symptoms of Exposure

For dibutyl phthalate - swallowing may cause nausea, dizziness - over exposure to hot vapors or mist may cause nose and throat irritation.

Medical Conditions Generally Aggravated by Exposure	Unknown
---	---------

Emergency and First Aid Procedures

Eyes - Flush with water for fifteen minutes and call physician. Skin - wash with soap and water. If ingested, induce vomiting and call physician at once.

Section VII -- Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled

Small spill - clean up with water before allowing to dry out. For large spill, dam up to prevent spread, ventilate area, scoop up material and place in suitable container, and wash up with water.

Waste Disposal Methods

Incinerate or bury in local landfill in accordance with local, state and federal regulations.

Precautions to be Taken in Handling and Storing

Prevent from freezing - store between 40° - 90° F. Keep containers closed to prevent drying out and microorganism contamination. Use adequate ventilation.

Other Precautions

Use with good ventilation when using large volumes, using in small area, or in spraying.

Section VIII -- Control Measures

Respiratory Protection (Specify Type)

Should be worn to prevent inhalation of spray mist or heated vapors.

Ventilation	Local Exhaust Recommended to control mist or vapors.	Special
	Mechanical (General) general ventilation for normal use.	Other

Protective Gloves Chemical resistant rubber or plastic when necessary

Eye Protection Goggles to prevent splashes in eyes.

Other Protective Clothing or Equipment

As needed to protect skin

Work Hygiene Practices

Use with good ventilation - avoid prolong or repeated contact with skin - avoid contact with eyes - do not take internally.